

WALL MOUNTED TYPE (COOLING ONLY) FTKE25/35G



Model name	Indoor unit		FTKE25GV1	FTKE35GV1
	Outdoor unit		RKE25GV1	RKE35GV1
Capacity	Rated (Min.-Max.)	kW	2.5 (1.6-3.2)	3.2 (1.6-4.0)
		Btu/h	8,500 (5,450-10,900)	10,900 (5,450-13,600)
Power supply			1 phase, 230 V, 50 Hz	
Running current	Rated	A	4.2	4.5
Power consumption	Rated (Min.-Max.)	W	746 (455-1,180)	955 (455-1,550)
	Rated	W/W	3.35	
Indoor unit			FTKE25GV1	FTKE35GV1
Front panel colour			White	
Airflow rate (H)		m ³ /min (cfm)	8.9 (314)	9.0 (318)
Fan speed			5 steps, quiet and automatic	
Sound levels (H/L/SL)		dB (A)	37/28/25	39/29/26
Dimensions (H x W x D)		mm	283 x 800 x 195	
Machine weight		kg	9	
Outdoor unit			RKE25GV1	RKE35GV1
Casing colour			Ivory white	
Compressor	Type		Hermetically sealed swing type	
	Motor output	W	600	
Refrigerant charge (R-22)		kg	0.67	0.77
Sound levels (H/SL)		dB (A)	47/43	48/44
Dimensions (H x W x D)		mm	550 x 765 x 285	
Machine weight		kg	30	32
Operation range		°CDB	19.4 to 46	
Piping connections	Liquid	mm	ø6.4	
	Gas		ø9.5	
	Drain		ø18.0	
Max. piping length		m	15	
Max. height difference			15	

Measurement conditions

1. Cooling capacity is based on: indoor temp. 27° CDB, 19° CWB; outdoor temp. 35° CDB; piping length 7.5m. 2. Sound levels are based on temperature conditions 1. These are anechoic conversion values. These values are normally somewhat higher during actual operation as a result of ambient conditions.