

Model name			Indoor unit
			Outdoor unit
<b>Power supply</b>			
			Power supply intake
Cooling capacity			kW
Rated			Btu/h
Power consumption			W
Cop			W/W
Operating current	Cooling		A
<b>Indoor unit</b>			
Panel color			
Dimensions (H x W x D)			mm
(Packaged Dimension)			mm
Weight (Gross)			Kg
Airflow rate			m <sup>3</sup> /min
Operation Sound H/M/L/SL	Cooling		dBA
<b>Outdoor unit</b>			
Dimensions (H x W x D)			mm
(Package dimensions)			mm
Weight (Gross)			Kg
Operation Sound H/L	Cooling		dBA
Breaker size			A
Piping length	Charge-less		m
	Max. length		m
	Max. height		m
Piping connection	Gas/Liquid		mm
Operation limit	Cooling		°CDB

FTF35SRV161	FTF50SRV162	FTF60SRV162
RF35SRV161	RF50SRV162	RF60SRV162
1Φ 50Hz 230V (220-240V)	1Φ 50Hz 230V (220-240V)	1Φ 50Hz 230V (220-240V)
Outdoor unit	Outdoor unit	Outdoor unit
3.35	5.2	6.4
11450	17750	21800
918	1425	1855
3.65	3.65	3.45
4.2	6.5	8.5
White	White	White
283 x 800 x 198	298 x 885 x 229	298 x 885 x 229
265 x 855 x 340	355 x 1010 x 390	355 x 1010 x 390
8 (12)	11(16)	11(16)
9.7	15.1	16.6
39/35/29/--	44/41/35/--	47/41/35/--
550 x 765 x 285	595 x 845 x 300	595 x 845 x 300
642 x 932 x 380	680 x 1035 x 410	680 x 1035 x 410
32 (40)	42 (51)	44(53)
49/--	50/--	56/--
15	15	20
10	10	10
20	20	20
15	10	10
Φ9.5/ Φ6.4	Φ12.7/ Φ6.4	Φ12.7/ Φ6.4
19.4~54	19.4~54	19.4~50

\*Not applicable for 1.8 ton model

#### Measurement conditions:

1. Cooling capacity is based on: indoor temp. 27° CDB, 19° CWB; outdoor temp. 35° CDB, piping length 5 m.

2. Sound levels are based on temperature conditions 1. above with 5m piping length. These are anechoic conversion values. These values are normally somewhat higher during actual operation as a result of ambient conditions.

Cooling and heating capacities above are rounded off to first decimal. 1TR (Ton of Refrigeration) = ~3.517 kiloWatt.

For the complete feature list please refer pages 39 – 42.