

CEILING MOUNTED SLIM DUCT TYPE



| | | Kit name | | | |
|--|---------------------------------------|------------|------------|------------|------------|
| | | Heat Pump | | | |
| | | FDXS25CVMA | FDXS35CVMA | FDXS50CVMA | FDXS60CVMA |
| Wired remote controller ¹ | | BRC944B2 | | | |
| Wired remote controller code | Length ³ m (shielded wire) | BRCW901A03 | | | |
| | Length ⁸ m (shielded wire) | BRCW901A08 | | | |
| 5-room centralised controller ² | | KRC72 | | | |
| Adaptor PCB (normal open/normal open pulse contact) ³ | | KRP413A1S | | | |
| The remote controller loss prevention with the chain | | KKF917A4 | | | |
| Interface adaptor for DIII-NET use | | KRP928B2S | | | |
| Central remote controller ⁴ | | DCS302CA61 | | | |
| Uni ed ON/OFF controller ⁴ | | DCS301BA61 | | | |
| Schedule timer ⁴ | | DST301BA61 | | | |
| Intelligent Touch Controller ⁴ | | DCS601C51 | | | |
| Suction grille | | KDG19A45 | | | |
| Insulation kit for high humidity | | KDT25N50 | | KDT25N63 | |

Note: ¹3 m (BRCW901A03) or 8 m (BRCW901A08) length wired remote controller cord is necessary .
required for each indoor unit.

²Adaptor PCB is also

³Time clock and other devices ; obtained locally.

⁴This optional accessory requires KRP928B2S